

Investigators: Wiley Evans (Hakai Institute), Katie Pocock (Hakai Institute), Shawn Hateley (Hakai Institute), and Jessy Barrette (Hakai Institute)

Title: Surface seawater and marine boundary layer CO₂ observations from October 2020 to September 2021 made from the Kwakshua Channel (KC) Buoy on the central coast of British Columbia

Abstract: Kwakshua Channel, located near Fitz Hugh Sound on the central coast of British Columbia, has been a site for moored, high-resolution measurements of surface seawater and marine boundary layer CO₂ content since May 2018. Measurements of in situ temperature, salinity, seawater and atmospheric CO₂ partial pressure are made using a Battelle Seaology (MApCO₂) System. This data contribution consists of measurements from October 27, 2020 to September 3, 2021.

Cite as: Evans, W., K. Pocock, S. Hateley, and J. Barrette (2022). Surface seawater and marine boundary layer CO₂ observations from October 2020 to September 2021 made from the Kwakshua Channel (KC) Buoy on the central coast of British Columbia. Version 1.0. Hakai Institute. Dataset. [access date].

Type of Study: Measurements of surface ocean and marine boundary layer CO₂ from a surface buoy

Temporal Coverage: October 27, 2020 to September 3, 2021

Spatial Coverage: Surface ocean and marine boundary layer CO₂ measurements from the mouth of Kwakshua Channel; Fitz Hugh Sound; central British Columbia coast; 51.6507°N, 127.9697°W

Geographic Names: Kwakshua Channel; Fitz Hugh Sound; central British Columbia coast; Gulf of Alaska; North Pacific Ocean

Expocode: 187F20201027

Platforms: KC Buoy

Version: 1.0

Submission Date: January 13, 2022

Change log:

This is Version 1.0 of this dataset. Data collected between January and May 2021 are believed to still on the platform and will be added to this dataset in a future submission.

Sampling frequencies:

Oct 2020 - Sep 2021: 1 hour

Data processing segments:

Oct 2020 - Jan 2021

May2021 - Sep 2021

Flagging windows:

Oct 2020 - Sep 2021: 3 points on either side of measurement

Dataset Metadata note:

As part of the QC process, a trend analysis is performed on the CO₂ measurements in which an average xCO₂ and standard deviation is computed over a set time window around each value (i.e. number of points on each side of the measurement). These values are then compared to the measured xCO₂ to determine whether the measurement should be flagged. Due to the variable nearshore environment of the deployment location, the flagging range used in the QC of this record was decreased from the default of 48 points on each side of the measurement (with a 3-hour sample frequency) to 3 points on each side of the measurement.

Filename: KC_BUOY_Oct2020_Sep2021.csv

Data dictionary / header information:

- (1) Mooring Name: Name/description of mooring
- (2) Latitude: Mooring latitude in decimal degrees
- (3) Longitude: Mooring longitude in decimal degrees
- (4) Date: UTC date (mm/dd/yyyy)
- (5) Time: UTS time (hh:mm)
- (6) xCO₂ SW (wet): (umol/mol) Mole fraction of CO₂ in air in equilibrium with the seawater at sea surface temperature and measured humidity
- (7) CO₂ SW QF: Flag for xCO₂ sw (wet)
- (8) H₂O SW: (mmol/mol) Mole fraction of H₂O in air from equilibrator
- (9) xCO₂ Air (wet): (umol/mol) Mole fraction of CO₂ in air from airblock, 4 feet above the sea surface at measured humidity.
- (10) CO₂ Air QF: Quality Flag for xCO₂ Air (wet)
- (11) H₂O Air: (mmol/mol) Mole fraction of H₂O in air from airblock, 4 feet above the sea surface.
- (12) Licor Atm Pressure: (hPa) Atmospheric pressure at the airblock, 4 feet above the sea surface.
- (13) Licor Temp: (C) Temperature of the Infrared Licor 820 in degrees Celsius.
- (14) MAPCO₂ %O₂: The percent oxygen of the surface seawater divided by the percent oxygen of the atmosphere at 4 feet above the sea surface. Disclaimer: The oxygen measurement is made in the equilibrated air and does not come to complete equilibrium therefore this measurement is qualitative and for diagnostic use only.
- (15) SST: (C) Sea Surface Temperature.
- (16) Salinity: Sea Surface Salinity on the practical scale.
- (17) xCO₂ SW (dry): (umol/mol) Mole fraction of CO₂ in air in equilibrium with the seawater at sea surface temperature (dry air).

(18) x_{CO_2} Air (dry): ($\mu\text{mol/mol}$) Mole fraction of CO_2 in air at the airblock, 4 feet above the sea surface (dry air).

(19) f_{CO_2} SW (sat): (μatm) Fugacity of CO_2 in air in equilibrium with the seawater at sea surface temperature (100% humidity). Since the measurements are taken at the sea surface, warming calculations are not necessary.

(20) f_{CO_2} Air (sat): (μatm) Fugacity of CO_2 in air at the airblock, 4 feet above the sea surface (100% humidity)

(21) df_{CO_2} : Difference of the fugacity of the CO_2 in seawater and the fugacity of the CO_2 in air (f_{CO_2} SW - f_{CO_2} Air).

(22) p_{CO_2} SW (sat): (μatm) Partial Pressure of CO_2 in air in equilibrium with the seawater at sea surface temperature (100% humidity)

(23) p_{CO_2} Air (sat): (μatm) Partial Pressure of CO_2 in air at the airblock, 4 feet above the sea surface (100% humidity).

(24) dp_{CO_2} : Difference of the partial pressure of CO_2 in seawater and air (p_{CO_2} SW - p_{CO_2} Air).

Researcher Contact: Please direct questions regarding these data to Wiley Evans (wiley.evans@hakai.org).

Researcher institution: Hakai Institute

Core Variables:

Seawater partial pressure of carbon dioxide at sea surface temperature

Abbreviation: p_{CO_2} SW (sat)

Unit: μatm

Observation type: Measurements from moored buoy with M Ap_{CO_2} system

In-situ/Manipulation/Response variable: In situ observation

Measured or calculated: Calculated from measured CO_2 mole fractions (x_{CO_2}) and ambient atmospheric pressure.

Sampling instrument: M Ap_{CO_2} equilibrator

Analyzing instrument: Battelle Seaology (M Ap_{CO_2}) System with LI-COR LI-820

Detailed sampling and analyzing information: All measurements are at sea surface temperature and atmospheric pressure. During the equilibration cycle, a closed loop of air equilibrates with seawater for 10 minutes. Once the equilibration period is complete, the pump stops and the system opens to the atmosphere allowing the pressure to equilibrate with atmospheric pressure. Measurements are recorded for 30 seconds at 2 Hz and then averaged. During the air cycle, fresh air is pumped through the detector for 1 minute. Once the pump stops, the system opens to the atmosphere allowing the pressure to equilibrate with atmospheric pressure. Measurements are recorded for 30 seconds at 2 Hz and then averaged. The gas streams for both the air cycle and equilibrator cycle are partially dried before entering the detector. The values listed as wet x_{CO_2} generally have relative humidity levels ranging from 40 to 80 percent. The humidity levels increase over the course of a deployment. Sampling occurs every 30 minutes. The infrared detector is calibrated at the beginning of every sampling period using a zero and span gas. To calculate the dry measurements, the water mole fraction in the Licor

detector is measured using a relative humidity sensor located immediately downstream of the detector.

Replicate information: N/A

Standardization description: Measurements calibrated using onboard zero and span gas with a known concentration. Span gases used to generate this dataset were 900 ppm from October 2020 to January 2021 (Praxair, Inc.), and 975 ppm from January 2021 to September 2021 (Praxair, Inc.).

Standardization frequency: Every measurement

CRM manufacturer: Praxair, Inc. and ESRL

Poison name: N/A

Poison volume: N/A

Poison correction: N/A

Uncertainty: 2 ppm for calibrated $x\text{CO}_2$; $\sim 2 \mu\text{atm}$ for $p\text{CO}_2$

Quality flag convention: No quality flag applied

Method reference: Sutton, A.J., Sabine, C.L., Maenner-Jones, S., Lawrence-Slavas, N., Meinig, C., Feely, R.A., Mathis, J.T., Musielewicz, S., Bott, R., Mclain, P.D., Fought, H.J., and Kozyr, A. (2014). A high-frequency atmospheric and seawater $p\text{CO}_2$ data set from 14 open-ocean sites using a moored autonomous system. *Earth System Science Data* 6, 353-366.

Researcher name: Wiley Evans

Researcher institution: Hakai Institute

Atmospheric partial pressure of carbon dioxide

Abbreviation: ATM $p\text{CO}_2$ wet

Unit: μatm

Observation type: Measurements from air intake on M/V Columbia foredeck

In-situ/Manipulation/Response variable: In situ observation

Measured or calculated: Calculated from measured CO_2 mole fractions ($x\text{CO}_2$) and ambient atmospheric pressure.

Sampling instrument: Air intake

Analyzing instrument: Battelle Seaology (MA $p\text{CO}_2$) with LI-COR LI-820

Detailed sampling and analyzing information: All measurements are at sea surface temperature and atmospheric pressure. During the equilibration cycle, a closed loop of air equilibrates with seawater for 10 minutes. Once the equilibration period is complete, the pump stops and the system opens to the atmosphere allowing the pressure to equilibrate with atmospheric pressure. Measurements are recorded for 30 seconds at 2 Hz and then averaged. During the air cycle, fresh air is pumped through the detector for 1 minute. Once the pump stops, the system opens to the atmosphere allowing the pressure to equilibrate with atmospheric pressure. Measurements are recorded for 30 seconds at 2 Hz and then averaged. The gas streams for both the air cycle and equilibrator cycle are partially dried before entering the detector. The values listed as wet $x\text{CO}_2$ generally have relative humidity levels ranging from 40 to 80 percent. The humidity levels increase over the course of a deployment. Sampling occurs every 30 minutes. The infrared detector is calibrated at the beginning of every sampling period using a zero and span gas. To calculate the dry measurements, the water mole fraction in the Licor detector is measured using a relative humidity sensor located immediately downstream of the detector.

Replicate information: N/A

Standardization description: Measurements calibrated using onboard zero and span gas with a known concentration. Span gases used to generate this dataset were 900 ppm from October 2020 to January 2021 (Praxair, Inc.), and 975 ppm from January 2021 to September 2021 (Praxair, Inc.).

Standardization frequency: Every measurement

CRM manufacturer: Praxair, Inc. and ESRL

Poison name: N/A

Poison volume: N/A

Poison correction: N/A

Uncertainty: 2 ppm for calibrated xCO₂; ~2 µatm for pCO₂

Quality flag convention: No quality flag applied

Method reference: Sutton, A.J., Sabine, C.L., Maenner-Jones, S., Lawrence-Slavas, N., Meinig, C., Feely, R.A., Mathis, J.T., Musielewicz, S., Bott, R., Mclain, P.D., Fought, H.J., and Kozyr, A. (2014). A high-frequency atmospheric and seawater pCO₂ data set from 14 open-ocean sites using a moored autonomous system. *Earth System Science Data* 6, 353-366.

Researcher name: Wiley Evans

Researcher institution: Hakai Institute

Sea surface temperature

Abbreviation: Intake T

Unit: °C, ITS-90 scale

Observation type: Measurements from surface buoy (1 m depth)

In-situ/Manipulation/Response variable: In situ observation

Measured or calculated: Measured

Sampling instrument: N/A

Analyzing instrument: SBE16plusV2

Detailed sampling and analyzing information: Data captured using a Campbell Scientific data logger onboard the surface buoy

Replicate information: N/A

Standardization description: N/A

Standardization frequency: N/A

CRM manufacturer: N/A

Poison name: N/A

Poison volume: N/A

Poison correction: N/A

Uncertainty: 0.005°C

Quality flag convention: No quality flag applied

Method reference:

Researcher name: Wiley Evans

Researcher institution: Hakai Institute

Seawater Salinity

Abbreviation: TSG Salinity

Unit: 1978 Practical Salinity Scale

Observation type: Measurements from surface buoy (1 m depth)

In-situ/Manipulation/Response variable: In situ observation

Measured or calculated: Calculated from conductivity and temperature measurements
Sampling instrument: N/A
Analyzing instrument: SBE16plusV2
Detailed sampling and analyzing information: Data captured using a Campbell Scientific data logger onboard the surface buoy
Replicate information: N/A
Standardization description: N/A
Standardization frequency: N/A
CRM manufacturer: N/A
Poison name: N/A
Poison volume: N/A
Poison correction: N/A
Uncertainty: 0.0005 S/m
Quality flag convention: No quality flag applied
Method reference:
Researcher name: Wiley Evans
Researcher institution: Hakai Institute