

GOES-16 ABI L2+ Shortwave Radiation Budget (SRB) Release  
Provisional Data Quality  
Oct 23, 2018  
Read-Me for Data Users

The GOES-R Peer Stakeholder - Product Validation Review (PS-PVR) for GOES-16 Advanced Baseline Imager (ABI) L2+ Shortwave Radiation Budget (SRB) Provisional Maturity was held on October 23, 2018. As a result of this review, the PS-PVR panel recommended that the ABI SRB product be declared Provisional Maturity.

The ABI L2+ SRB product includes the Reflected Shortwave Radiation: Top of Atmosphere (RSR) and the Downward Shortwave Radiation: Surface (DSR), associated quality flags, mean, maximum, minimum and standard deviation. RSR and DSR are, respectively, the instantaneous shortwave (0.2 – 4.0  $\mu\text{m}$ ) radiative fluxes reflected to space at the top of atmosphere (TOA) and transmitted to the Earth's surface. Both are reported in units of  $\text{W m}^{-2}$ .

- *Measurement range:* 0 to 1300  $\text{W m}^{-2}$  for RSR and 0 to 1500  $\text{W m}^{-2}$  for DSR.
- *Temporal coverage:* RSR and DSR retrievals are produced only during daytime with solar zenith angles less than 90 degrees.
- *Refresh:* RSR and DSR are produced once per hour; they represent instantaneous fluxes at the time indicated in the files, they are not hourly averages.
- *Spatial coverage:* RSR is produced in the Full Disk (FD) and in the Continental United States (CONUS) domains. DSR is produced in FD, CONUS, and Mesoscale domains.

Retrievals are performed for all daytime grid-cells containing any mixture of clear and cloudy pixels both over land and water.

Low solar and satellite elevation (zenith angle larger than  $70^\circ$ ) reduces the spatial coverage in the good-quality RSR and DSR data.

- *Spatial resolution:* RSR is produced on a global equal-angle latitude/longitude grid at a 0.05-degree (25 km) spatial resolution in the FD and CONUS domains. DSR is also produced on a global equal-angle latitude/longitude grid but at a 0.50-degree (50 km) resolution for FD, at 0.25-degree (25 km) for CONUS, and at 0.05-degree (5 km) for the Mesoscale domain.
- *Quality:* A preliminary evaluation of GOES-16 RSR and DSR with RSR from the NASA Fast Longwave And SHortwave Radiative Fluxes (FLASHFlux) product and with DSR measured at the ground in the Surface Radiation Budget Network (SURFRAD) and the Solar Radiation Network (SOLRAD) indicates that the mean biases are less than  $60 \text{ W m}^{-2}$ . In the low and mid ranges (fluxes less than about  $500 \text{ W m}^{-2}$ ) the biases are positive and generally less than  $30 \text{ W m}^{-2}$ , they become negative in the high range. The standard deviation of biases are less than  $130 \text{ W m}^{-2}$ .

In general, the good quality retrievals are recommended for quantitative applications due to their better overall performance. The performance is expected to be further improved by updating the way

the TOA broadband (shortwave) albedo needed in the retrieval process is determined from the narrow-band ABI reflectances.

The product quality is sensitive to upstream processing, such as the quality of calibration, navigation, cloud mask, snow mask and total precipitable water.

Full description and format of the RSR and DSR products is in the Product Definition and User's Guide (PUG) document (<http://www.goes-r.gov/products/docs/PUG-L2+-vol5.pdf>). The algorithms used for deriving RSR and DSR from ABI observations are described in the "GOES-R Advanced Baseline Imager (ABI) Algorithm Theoretical Basis Document for Downward Shortwave Radiation (Surface), and Reflected Shortwave Radiation (TOA)" (<https://www.goes-r.gov/products/ATBDs/baseline/baseline-DSR-v2.0.pdf>).

Provisional maturity, by definition, means that:

- Validation activities are ongoing and the general research community is now encouraged to participate;
- Severe algorithm anomalies are identified and under analysis. Solutions to anomalies are in development and testing;
- Incremental product improvements may still be occurring;
- Product performance has been demonstrated through analysis of a small number of independent measurements obtained from select locations, periods, and associated ground truth or field campaign efforts;
- Product analysis is sufficient to establish product performance relative to expectations (Performance Baseline);
- Documentation of product performance exists that includes recommended remediation strategies for all anomalies and weaknesses. Any algorithm changes associated with severe anomalies have been documented, implemented, tested, and shared with the user community;
- Testing has been fully documented; and
- Product is ready for operational use and for use in comprehensive cal/val activities and product optimization.

Users bear all responsibility for inspecting the data prior to use and for the manner in which the data are utilized. Persons desiring to use the GOES-16 ABI RSR and DSR products for any reason, including but not limited to scientific and technical investigations, are encouraged to consult the NOAA algorithm working group (AWG) scientists for feasibility of the planned applications.

Known product issues:

1. MESO DSR product may have large errors due to currently low-quality broadband clear-sky composite TOA albedo needed in the retrieval.
2. Incorrect statistics (mean, maximum, minimum and standard deviation) in mode 4 CONUS metadata.
3. MESO DSR occasionally may include only fill values.

4. Inconsistent units (percent) and valid range (0, 1) in some metadata variables. For example, variable “image\_cloud\_fraction” states the units are percent, but the data are fraction within 0 and 1.
5. The variable “algorithm\_dynamic\_input\_data\_container”, meant to list names of dynamic input data files required to run the SRB algorithm, is currently not set (null) for dynamic NWP total column ozone and total precipitable water.

Known PUG issues:

1. Accuracy and precision requirements for low end RSR are missing from Table 5.25.1. Accuracy: 110 W/m<sup>2</sup> at low end of range (<200 W/m<sup>2</sup>); Precision: 100 W/m<sup>2</sup> for low end of range (<200 W/m<sup>2</sup>).

Contact for further information: OSPO User Services at [SPSD.UserServices@noaa.gov](mailto:SPSD.UserServices@noaa.gov)

Contacts for specific information on the ABI L2 SRB product:

Jaime Daniels [jaime.daniels@noaa.gov](mailto:jaime.daniels@noaa.gov)

Istvan Laszlo [istvan.laszlo@noaa.gov](mailto:istvan.laszlo@noaa.gov)